




NOTES:
Pitch : 5.0mm
Rated Voltage : 250V
Rated Current : 32A
Withstand Voltage :
AC2500V for 1 minute
Insulation Resistance :
500MΩ / DC500V
Using Temperature Range :
- 40℃ ~ + 105℃
Wire range : 24~ 14AWG

技术要求:

间距: 5.0mm

额定电压: 250V


额定电流: 32A

耐电压值: AC2500V/min

绝缘阻抗: 500M Ω /DC500V

使用条件: -40℃~+105℃

适用线规: 24~14AWG



5	J2-2-导电线	60J2BDD032AV-1	P	黄铜	镀镍
4	J2-2-弹片	60J2TDD032AV-1	2P	不锈钢	
3	J2-2-手柄	60J200Y0323V-1	2P	PA66-V0	
2	J3-3-盖板	60J3C910323V-1	1	PA66-V0	
1	J3-3-本体	60J3A910323V-1	1	PA66-V0	
NO.	NAME OF PART	NO. OF PART	Q' TY	MATERIAL	NOTES
DES.	WY	DATE	2022/06/21	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1: 1
 上海联捷电气有限公司 Shanghai Elinker Electric Co., LTD				TITLE	J3-3-1120-00A
					J3-3-1120-成品