



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
Pitch : 2.5mm
Rated Voltage : 150 V
Rated Current : 4A
Withstand Voltage :
AC2000V for 1 minute
Insulation Resistance :
500MΩ / DC500V
Using Temperature Range :
- 40℃ ~ + 105℃
Wire range :24 ~20 AWG

技术要求:
间距: 2.5mm
额定电压: 150V
额定电流: 4A
耐电压值: AC2000V/min
绝缘阻抗: 500MΩ/DC500V
使用条件: -40℃~+105℃
适用线规: 24~20 AWG

	pitch dimension			Nominal dimension					
variable range	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	— ▱ ⌒
	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

5	LC6-2.5-弹片	F2A0DLC625BV	P	不锈钢	
4	LC6-2.5-夹子	1023B0001AV	P	黄铜	镀镍
3	LC6-2.5-按钮	1023D0YXXAV	p	PA66	
2	LC6-2.5-盖板	1023C0YXXAV	1	PA66	
1	LC6-2.5-主体	1023A0YXXAV	1	PA66	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	ARKTIB	DATE	12-02-23	UNITS	mm
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
DWG NO.				SP-2-1023001	REV: V0
上海联捷电气有限公司 Shanghai Elinker Electric CO., LTD				TITLE	LC6-2.5-XXP-1Y-00A LC6-2.5-成品