




REVISION RECORD			
REV.	CONTENT	MOD.	DATE
	初版发行		



NOTES:

1. Voltage Rating: 400V, Current Rating: 20A
2. PITCH: 7.62mm
3. Insulation Withstands Voltage: AC2500V/min
4. Insulation Resistance: 500MΩ or more at DC500V
5. Using Temperature Range: -40℃- +105℃
6. Suitable Electric Wire: 22-14AWG



技术要求:

1. 额定电压: 400V, 额定电流: 20A
2. 间距: 7.62mm
3. 耐电压值: AC 2500V/min
4. 绝缘阻抗: 500兆欧
5. 使用条件: -40℃- +105℃
6. 适用线规: 22-14AWG

	pitch dimension			Naminal dimension					
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

7	LSC10-7.62-本体	1097A0Y01AV	P-1	PA66	
6	LSC10-方针	1062B0001AV	P	紫铜	镀雾锡
5	LSC1-弹片	F2A0DLSLC1BV	P	不锈钢	
4	LSZ1-7.62-主体	1092A0YXXAV	1	PA66	
3	LSC10M-5.08-盖板2	1064C0Y01AV	1	PA66	
2	LSC10M-5.08-盖板1	1063C0Y01AV	1	PA66	
1	LSC10-5.08-本体	1062A0Y01AV	1	PA66	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	LDD	DATE	2013/02/21	UNITS	mm
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				TITLE	LSC10M-7.62-XXP-1Y-00A
上海联捷电气有限公司 Shanghai Elinker Electric CO.,LTD					LSC10M-7.62-成品