




REVISION RECORD			
REV.	CONTENT	MOD.	DATE
	初版发行		



NOTES:

1. Voltage Rating: 400V, Current Rating: 20A
2. PITCH: 7.50mm
3. Insulation Withstands Voltage: AC2500V/min
4. Insulation Resistance: 500MΩ or more at DC500V
5. Using Temperature Range: -40℃ - +105℃
6. Suitable Electric Wire: 22-14AWG

技术要求:

1. 额定电压: 400V, 额定电流: 20A
2. 间距: 7.50mm
3. 耐电压值: AC 2500V/min
4. 绝缘阻抗: 500兆欧
5. 使用条件: -40℃- +105℃
6. 适用线规: 22-14AWG

	pitch dimension			Nominal dimension					
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

6	LSC10-7.5-本体	1097A0Y01AV	P-1	PA66	
5	LSC10-方针	1062B00010V	P	黄铜	镀雾锡
4	LSC1-弹片	F2A0DLSLC1BV	P	不锈钢	
3	LSZ10-7.5-主体	1095A0YXXAV	1	PA66	
2	LSC10-5.08-盖板	1062C0Y01AV	1	PA66	
1	LSC10-5.0-本体	1069A0Y01AV	1	PA66	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	LDD	DATE 2013/02/21	UNITS mm	THIRD ANGLE PROJECTION	
CHK.		DATE	SIZE A4		SHEET 1 of 1
APP.		DATE	SCALE	DWG NO.	SP-2-1095001 REV: V0
上海联捷电气有限公司 Shanghai Elinker Electric CO.,LTD				TITLE	LSC10-7.5-XXP-1Y-00A LSC10-7.5-成品