






REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		



NOTES:
 Pitch : 5.0mm
 Rated Voltage : 300 V
 Rated Current : 10A
 Withstand Voltage : AC2500V for 1 minute
 Insulation Resistance :500MΩ / DC500V
 Using Temperature Range : - 40℃ ~ + 105℃
 Wire range :26 ~14 AWG
 Screw Torque Value : 0.4Nm



技术要求:
 间距: 5.0mm
 额定电压: 300V
 额定电流: 10A
 耐电压值: AC2500V/min
 绝缘阻抗: 500MΩ/DC500V
 使用条件: -40℃~+105℃
 适用线规: 26~14AWG
 螺丝扭矩: 0.4Nm



	pitch dimension			Nominal dimension					— /
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		— /
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10




5	LC-耳朵螺丝	SP0YA255101V	2P	碳钢	三价铬钝化彩锌
4	LG128-铜方块	F1A0BLG1283V	2P	黄铜	镀镍
3	LG500-中焊脚	2042B0002AY	P	黄铜	镀雾锡
2	LG128-V焊脚	2013B0001AY	P	黄铜	镀雾锡
1	LG500AZL-5.0-主体	2042A0YXXAY	1	PA66	
NO.	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
DES.	ARKING	DATE 2011/10/23	UNITS mm	THIRD ANGLE PROJECTION	SHEET
CHK.		DATE	SIZE A4		1 of 1
APP.		DATE	SCALE 1:1	DWG NO. SP-2-2042001	REV: V0
上海联捷电气有限公司 Shanghai Blinker Electric CO.,LTD				TITLE	LG500AZL-5.0-2*XXP-1Y-00A LG500AZL-5.0-成品

REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		



NOTES:
Pitch : 5.0mm
Rated Voltage : 300 V
Rated Current : 10A
Withstand Voltage : AC2500V for 1 minute
Insulation Resistance :500MQ / DC500V
Using Temperature Range : - 40℃ ~ + 105℃
Wire range :26 ~14 AWG
Screw Torque Value : 0.4Nm

技术要求:
间距: 5.0mm
额定电压: 300V
额定电流: 10A
耐电压值: AC2500V/min
绝缘阻抗: 500MΩ/DC500V
使用条件: -40℃~+105℃
适用线规: 26~14AWG
螺丝扭矩: 0.4Nm



	pitch dimension			Nominal dimension					— /
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		— /
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

5	LC-耳朵螺丝	SP0YA255101V	2P	碳钢	三价铬钝化彩锌
4	LG128-铜方块	F1A0BLG1283V	2P	黄铜	镀镍
3	LG500-中焊脚	2042B0002AV	P	黄铜	镀雾锡
2	LG128-V焊脚	2013B0001AV	P	黄铜	镀雾锡
1	LG500AZL-5.08-主体	2048A0YXXAV	1	PA66	
NO.	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
DES.	ARKINB	DATE 2011/10/23	UNITS	mm	THIRD ANGLE PROJECTION
CHK.		DATE	SIZE	A4	1 of 1
APP.		DATE	SCALE	1:1	DWG NO. SP-2-2040001 REV: V0
上海联捷电气有限公司 Shanghai Elinker Electric CO.,LTD				TITLE	LG500AZL-5.08-2*XXP-1Y-00A LG500AZL-5.08-成品