


NOTES:
Pitch : 7.0mm
Rated Voltage : 380V
Rated Current : 8A
Withstand Voltage :
AC2500V for 1 minute
Insulation Resistance :
500MΩ / DC500V
Using Temperature Range :
- 40℃ ~ + 105℃
Wire range : 24~ 16AWG

间距: 7.0mm
额定电压: 380V
额定电流: 8A
耐电压值: AC2500V/min
绝缘阻抗: 500MΩ/DC500V
使用条件: -40℃~+105℃
适用线规: 24~16AWG

5	H3800导电件		4020B0001AV		P	黄铜	镀镍
4	LC1-3.81-铜方块		F1A0BLC3813V		2P	黄铜	镀镍
3	LC1-3.81-螺丝(一字平头)		SP0YA204801V		2P	碳钢	三价铬钝化彩锌
2	H3800-C-盖板		4022C4002AV		1	PA66-V0	
1	H3800-C-本体		4022A4002AV		1	PA66-V0	
NO.	NAME OF PART		NO. OF PART		Q'TY	MATERIAL	NOTES
DES.	WY	DATE	2021/5/12	UNITS	MM		SHEET
CHK.		DATE		SIZE	A4		1 of 1
APP.		DATE		SCALE	1:1		
 上海联捷电气有限公司 Shanghai Elinker Electric C O., LTD						TITLE	H3800-C-2P-1Y-00A
							H3800-C-2P-成品